

JUPITAIR 2400-50

REF. AC017825-1

HEAT PUMP
2400 WATT CAPACITY
REMOTE CONTROL
WORKS UP TO 54°C OUTSIDE TEMPERATURE



Cooling capacity		2,40 kW (8200 BTU/h)
Heating capacity		2,40 kW (8200 BTU/h)
Power supply		220-240 V, 50 Hz, 1 phase
Fuse		6 A
Start-up amps		16 A (up to) / 0,15 s.
Amps cooling	at 35°C and 50% humidity	4,1 A
Amps cooling	at 45°C and 30% humidity	5,1 A
Amps Heating		3,7 A
Power consumption cooling	at 35°C and 50% humidity	940 W
Power consumption cooling	at 45°C and 30% humidity	1170 W
Power consumption heating		850 W
Refrigerant		R 407C
Ventilation speeds		3 + auto mode
Maximum air flow		367 m3/h
Dimensions	Roof unit	L 108 x W 57 x H 25 cm
Dimensions	Ceiling Assembly	L 54 x W 54 x H 4 cm
Roof opening		40 x 40 cm
Roof thickness		up to 8 cm
Weight	Roof unit	28 Kg
Weight	Ceiling Assembly	5,- Kg

JUPITAIR 3600-50

REF. AC3600-230



HEAT PUMP
3600 WATT CAPACITY
REMOTE CONTROL
WORKS UP TO 54°C OUTSIDE TEMPERATURE

Cooling capacity		3,60 kW (12300 BTU/h)
Heating capacity		3,60 kW (12300 BTU/h)
Power supply		220-240 V, 50 Hz, 1 phase
Fuse		10 A
Start-up amps		20 A (up to) / 0,15 s.
Amps cooling	at 35°C and 50% humidity	5,2 A
Amps cooling	at 45°C and 30% humidity	7,2 A
Amps Heating		5,0 A
Power consumption cooling	at 35°C and 50% humidity	1200 W
Power consumption cooling	at 45°C and 30% humidity	1600 W
Power consumption heating		1200 W
Refrigerant		R 407C
Ventilation speeds		3 + auto mode
Maximum air flow		540 m3/h
Dimensions	Roof unit	L 113 x W 86 x H 29 cm
Dimensions	Ceiling Assembly	L 54 x W 54 x H 4 cm
Roof opening		40 x 40 cm
Roof thickness		up to 8 cm
Weight	Roof unit	40 Kg
Weight	Ceiling Assembly	5,- Kg